

CARTRIDGE FILTER HOUSING



This design has been a standard in the industry for over 40 years. The housing is available in either carbon steel or stainless steel. Maximum operating pressure is 250 psi and standard operating temperature is 275°F. This housing is available with 1" NPT connections only.

DESIGN FEATURES

- Designed for industrial and commercial filtration applications
- Heavy duty construction for durability
- Offered in carbon steel or 304 stainless steel
- Simple nut and bolt design for quick cartridge change outs
- In-line fittings for easy installation
- Knife edge seal at both cartridge ends to eliminate bypass
- Designed for double open end cartridges
- 1" NPT pipe size standard
- 1/8" NPT drain port on bottom of housing

TYPES OF CARTRIDGES AVAILABLE

- Flow Ezy's all stainless steel industrial process cartridges
- Flow Ezy's A2 model fabric wound 9-7/8" cartridges
- Flow Ezy's meltblown 9-7/8" cartridges
- Any other 9-7/8" double open end cartridge with an ID of 1-1/8" and an OD of no larger than 3"



**Order Cartridges
 on pages
 30, 31, and 32**

HOW TO ORDER

Order by model number:

MODEL NUMBER	DESCRIPTION
FAC788	Carbon steel
FAS788	304 stainless steel