

Filter Media Specifications

Standard Media

5 µm Polyester, 5 micron, 99+% efficiency

- ID: "odd nbr.": i.e. **19, 235P**
- Classification: ePM₁₀ 75% (ISO 16890)
- Pleated industrial needle felt polyester media
- Plastisol potting
- Temperature min: -26°C (-15°F), max: 104°C (220°F)
- Reinforced epoxy coated steel wire on ID and OD

2 µm Paper, 2 micron, 99+% efficiency

- ID: "even nbr.": i.e. **18, 234P**
- Classification: ePM_{2.5} 50% (ISO 16890)
- Heavy duty industrial strength paper
- Plastisol potting
- Heavy gauge galvanized expanded metal
- Temperature min: -26°C (-15°F), max: 104°C (220°F)

High Efficiency

1 µm Polyester - Z Media, 1 micron, 99+% efficiency

- ID: "odd nbr." & "Z" suffix: i.e. **19Z, 235ZP**
- Classification: ePM_{2.5} 60% (ISO 16890)
- Epoxy coated steel wire on both sides of media
- Temp min: -26°C (-15°F), max: 104°C (220°F)
- Washable - lukewarm water & mild detergent

4 µm Polyester - N Media, 4 micron, 99+% efficiency

- ID: "odd nbr." & "N" suffix: i.e. **15N, 377NP**
- Temp min: -26°C (-15°F), max: 104°C (220°F)

E12 - HE Media, 0.3 um, 99,97%

- ID: "HE" prefix & "even nbr.": i.e. **HE230, HE334P**
- Classification: E12 under EN 1822/ISO 30E under ISO 29463
- Heavy duty industrial strength glass surrounded by heavy gauge galvanized expanded metal
- Maximum oversizing required to minimize pressure drop
- Plastisol potting standard
- Temp min: -26°C (-15°F), max: 104°C (220°F)
- Options: silicone potting, viton gaskets, temp max: 190°C (375°F)

H14 - UL Media, 0.1 micron, 99.995% efficiency

- ID: "UL" prefix & "even nbr.": i.e. **UL234**
- Classification: H14 under EN1822/ISO45H under ISO 29463
- Plastisol potting
- Temp min: -26°C (-15°F), max: 104°C (220°F)
- Options: silicone potting, viton gaskets, temp max: 190°C (375°F)

■ **Dutch Twill Weave - DT Media**

- ID: "DT" prefix & "odd nbr.": i.e. **DT245**
- Classification: ePM₁₀ 70% (ISO 16890)
- Stainless steel woven wire cloth
- Viton gaskets & epoxy potting
- Temp min: -26°C (-15°F), max: 190°C (375°F)

Chemical / Food / Pharmaceutical

Stainless Steel Wire Mesh - S2 Media

- Stainless steel pleated wire mesh
- ID: "even nbr." & "S2" suffix: i.e. **14S2**
- Stainless steel expanded metal
- Chemical resistant and high temperature resistant
- Available with silicone endcaps

Polypropylene (PP) - Y Media, 5 micron, 99+% efficiency

- ID: "odd nbr." & "Y" suffix: i.e. **31Y, 345YP**
- Epoxy coated steel wire on ID and OD

PTFE - TG Media, 0.3 micron, 99.5% efficiency

- ID: "TG" prefix & "odd nbr.": i.e. **TG375**
- Classification: E11 under EN1822/ISO 15E under ISO 29463
- High temperature, chemical, & moisture resistant
- Options: viton gaskets, epoxy potting
- Temp (intermittent): Up to 250°C (482°F)

PTFE - TF Media, 0.3 micron, 99.5% efficiency

- ID: "TF" prefix & "odd nbr.": i.e. **TF275**
- Classification: E11 under EN1822/ISO 15E under ISO 29463
- Chemical & moisture resistant
- Minimal pressure drop
- Temp (intermittent): 104°C (220°F)
- Options: viton gaskets, epoxy potting

PPS - RY Media

- Broad chemical resistant media, high temp
- ID: "RY" prefix & "odd nbr.": i.e. **RY485**
- Temp min: -15°F (-26°C), max: 220°F (104°C)
- Options: viton gaskets, epoxy potting

Coarse Efficiency

25 µm Polyester - U Media, 25 micron, 99+% efficiency

- ID: "odd nbr." & "U" suffix: i.e. **19U, 685UP**
- Temp min: -26°C (-15°F), max: 104°C (220°F)

100 µm Polyester - W Media, 100 micron, 99+% efficiency

- ID: "odd nbr." & "W" suffix: i.e. **15W, 385WP**
- Temp min: -26°C (-15°F), max: 104°C (220°F)

Wire Mesh - S Media

- Epoxy coated pleated wire mesh
- ID: "even nbr." & "S" suffix: i.e. **274S, 344SP**
- Expanded metal
- Temp min: -26°C (-15°F), max: 104°C (220°F)

Stainless Steel - S2 Media

- Stainless steel pleated wire mesh
- ID: "even nbr." & "S2" suffix: i.e. **234S2**
- Chemical resistant and high temperature resistant
- Stainless steel expanded metal
- Temp min: -26°C (-15°F), max: 104°C (220°F)
- Options: silicone or epoxy potting, viton gaskets

High Temperature

Nomex - MX Media, 5 Micron, 99+% efficiency

- ID: "odd nbr." & "MX" suffix: i.e. **377MX**
- Classification: ePM₁₀ 80% (ISO 16890)
- Silicone potting
- Temperature min: -15°F (-26°C), max: 385°F (196°C)
- Reinforced epoxy coated steel wire on ID and OD

Nomex with Stainless Steel Support - MXD Media

- 5 micron, 99+% efficiency
- ID: "odd nbr." & "MX" suffix: i.e. **377MXD**
- Classification: ePM₁₀ 80% (ISO 16890)
- Silicone potting
- Reinforced stainless steel wire mesh on ID and OD
- Temperature min: -26°C (-15°F), max: 196°C (385°F)

Note 1: Elements rated for higher temperatures can be achieved with optional gasket material and potting compounds.

Note 2: Classifications are best estimates based on ISO 16890-1:2016.

Chemical Adsorption

Activated Carbon - AC Media, 10 micron, 99+% efficiency

- ID: "AC" prefix & "even nbr.": i.e. **AC18**
- Removes gas or vapor odors, contaminants, & particulate
- Pleated media
- Reinforced with epoxy coated steel wire on both sides of cloth

Activated Carbon Granulate - ACG Media

- ID: "ACG" prefix & "even nbr.": i.e. **AC30**
- Removes gaseous or vapor odors
- Granulates are enclosed within a polyester wrap and expanded metal on the ID and OD

Activated Alumina - AA Media

- ID: "AA" prefix & "even nbr.": i.e. **AA850**
- Desiccant used in the adsorption of water & oil vapor and the prevention of backstreaming in pumps
- Adsorbs up to 40% of media's weight

Electrostatic Activated Carbon - GM Media

- 3 micron, 70% efficiency
- ID: "GM" prefix & "odd nbr.": i.e. **GM35**
- Superior odor removal
- Chemically inert
- Electrostatic fibers attract & hold particles

Coalescing Media

PSG Media, FG Media, GL Media

- 0.3 micron, 99.97% efficiency
- ID: "PSG" prefix & "even nbr.": i.e. **PSG344**
- ID: "FG" prefix: i.e. **FG9**
- ID: "GL" prefix: i.e. **GL915**
- Heavy duty industrial glass media, reinforced with epoxy coated steel wire & expanded metal
- Continuous operating temp: 20°C (68°F) to 80°C (180°F)
- Environmentally friendly sealing material
- High D.O.P. efficiency - low oil carryover
- Multiple media configurations, contact factory



Rev: Media-EU0220K



SOLBERG

All model offerings and design parameters are subject to change without prior notice.
Contact your representative or Solberg for the most current information.

www.nsltechnology.com